

FOA-MSDS-02

Revision: 00

Validity: 20/12/2022

1. PRODUCT AND COMPANY IDENTIFICATION		
NAME:	DISPOSABLE ELECTRONIC CIGARETTE PARTY 1800.	
BRAND:	ZOMO	
MANUFACTER:	FLAVORS OF AMERICAS S.A.	
ADDRESS:	Av. Herminio Giménez esq. Monseñor Rodríguez – Km 4,5 – Ciudad del Este, Paraguay	
PHONE NUMBER:	+595961574188	
EMERGENCY:	Medical Emergency Center Toxicology Service +595 21 220418	

# 2. PRODUCT SPECIFICATIONS

DISPONSABLE PARTY ZOMO is an electronic cigarette for vaping with 1800 puffs of pure flavor, with an internal 900mAh disposable battery with a voltage of 3.7 volts.



PRODUCT	WATERMELON ICE	2%		
Ingredients	Chemical Name	CAS Number	Concentration	
Propylene glycol	1,2-propanediol	57-55-6	35 - 50 %	
Gliceryne	1,2,3-propanetriol	56-81-5	35 - 50 %	
Watermelon Flavouring	N/A	N/A	6 - 10 %	
Nicotine	Nicotine	54-11-5	2 %	
Lactic Acid	Lactic Acid	50-21-5	0.7 - 0.9%	
MECHANICAL AND ELECTRICAL DATA				
Size	22.4mm*13.4mm*116.8mm			
Weight	43,71 grams			

Weight	43,71 grams
Material	Polycarbonate
Battery capacity	900mAh Li-ion battery cell
Puffs	1800
Tank Volume	5,0 mL



FOA-MSDS-02

Revision: 00

Validity: 20/12/2022

Operational mode	Automatic firing by switch
Turn on/Turn off	NA
Display	LED light
Battery Display	The battery display LED indicator light will turn on and off gradually when you
	start/stop vaping, the LED light will stay green during vaping.
Operational mode	Automatic firing by switch
Short Circuit	When a short circuit occurs during operation (the detected resistance is less
Protection	than 1.0 ohm) the light will turn green for 2 seconds and automatically cut off
	the device operation.
Atomizer protection	If vaping continuously for more than 8 seconds, the LED light will flash twice
	and stop vaping.
Low voltage protection	When the battery voltage is 3.3V, the LED light will flash 10 times and then
	stop automatically.

#### 3. HAZARDS IDENTIFICATION

Classification of the substance or mixture:

Primary Hazardous Component:

- Nicotine
- Acute toxicity, Category 3, Oral, H301
- Acute toxicity, Category 1, Dermal, H310

Hazard pictograms:



#### Signal word: DANGER

Hazard Statements:

- Toxic swallowed
- Fatal in contact with skin

Precautionary statements- General:

- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Read label before use.

Precautionary statements- Prevention: Wear protective gloves/protective clothing/eye protection/face protection.



FOA-MSDS-02

Revision: 00

Validity: 20/12/2022

Precautionary statements- Response:

- IF ON SKIN: Wash with plenty of soap and water.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- Remove/Take off immediately all contaminated clothing.
- Wash contaminated clothing before reuse.

Precautionary statements - Disposal: Dispose of contents and container to an approved waste disposal plant.

## 4. MODE OF USE

Remove the product from the box, remove the upper protective cover and inhale for a few seconds to vape.

### 5. INDICATIONS

- Prohibited the sale and supply to minors under 18 years of age. .
- Keep out of the reach of children.
- Keep away from heat.
- Store in a clean and dry place..

## 6. PRESENTATION

- 10 units per display.
- 10 displays per master box.

## 7. FIRE FIGHTING MEASURE

Suitable Extinguishing Agents: In case of fire, use carbon dioxide (CO2).Unsuitable

Extinguishing: A solid water stream may be inefficient.

Special Hazards:

- Thermal decomposition can lead to release of irritating gases and vapors.
- Exposure to products decomposition may be a hazard to health.
- Do not breathe smokes.

### 8. ACCIDENTAL RELEASE MEASURES

- Small Spill: Dilute with water and mop up or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of according to local, state, and federal regulations.
- Large Spill: Stop leak if without risk. Do not get water inside container. Do not touch spilled material. Use a light water spray to reduce vapors. Prevent entry into sewers, basements, or confined areas: dike if needed. Eliminate all ignition sources. Mop up while diluting with water, or absorb with an inert dry material such as sand, cat litter, diatomite, sawdust, etc. Collect and place in bags and dispose of according to local, state, and federal regulations.



Revision: 00

Validity: 20/12/2022

### 9. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection: Under normal conditions protection is not necessary. In case of intense or long exposure, use special mask with filter.
- General protective and hygiene measures: Avoid skin, eye, and clothing contact. Wash hands before and after handling.
- Skin Protection: Wear gloves impermeable to material.

### 10. PHYSICAL AND CHEMICAL PROPERTIES

- Physical State: Solid
- Odor: Varies from odorless to slight
- Color: Black
- pH: Not available
- Density: 0.994 1.014 kg / l
- Solubility in water: Not available
- Viscosity: Not available

### 11. STABILITY AND REACTIVITY

- Chemical Stability: Stable under normal conditions.
- Conditions of Instability: Heat, fire or other ignition sources, incompatible materials.
- Incompatible Materials: Reacts with oxidizing agents and acids.

#### 12. TOXICOLOGICAL INFORMATION

#### Nicotine, USP:

- Oral, Rat: LD50 = 70 mg/kg
- Dermal, Rat: LD50 = 140 mg/kg
- Dermal, Rabbit: LD50 = 50 mg/kg

### Propylene Glycol, USP:

- Oral, Rat: LD50 = 20 000 mg/kg
- Oral, Mouse: LD50 = 22 000 mg/kg
- Dermal, Rabbit: LD50 = 20 800 mg/kg

### 13. ECOLOGICAL INFORMATION

Environmental exposure controls: Should not be allowed to reach large quantities of ground water, sewage, wastewater, or soil.

#### 14. DISPOSAL CONSIDERATIONS

Method of disposal: Spilled, contaminated, or residual material should be placed in a suitable container. Disposal of contaminated packaging:

- Empty container completely. Keep label(s) on container.
- Containers should be disposed of in accordance with current regulations.



15. TRANSPORT INFORMATION

FOA-MSDS-02

Revision: 00

Validity: 20/12/2022

- UN-Number: UN 1654
- Class: 6.1
- Classification code: T1
- Packing group: II

7. EXPIRATION

- 3 years from its manufacture.

